

# R | BOUNCE BACK 6.5 PRODUCT SPECIFICATIONS



<b>COLLECTION</b>	Bounce Back
<b>STYLE NUMBER</b>	I208V
<b>CONSTRUCTION</b>	Commercial Heterogeneous Sheet
<b>WEAR LAYER THICKNESS</b>	39 mil / 0.039 inches (0.991 mm)
<b>OVERALL THICKNESS</b>	0.256 inches (6.5 mm)
<b>REFERENCE SPECIFICATION</b>	ASTM F2772
<b>BACKING CLASS</b>	Closed Cell Foam
<b>FINISH</b>	UV Urethane
<b>INSTALLATION TYPE</b>	Dry Back
<b>INSTALLATION</b>	Glue Down
<b>RECOMMENDED ADHESIVE</b>	LOKWORX+ RESILI or 4151

## Packaging

### ROLL SIZE

### US Units

70 inches W x 49 ft L  
32.22 sq yds/roll

### Metric Units

1.8 m W x 14.9 m L  
26.9 sq m/roll

### PIECES /BOX

12

### AREA /BOX

32.22 sq yds

26.9 sq m

### WEIGHT /ROLL

253.6 lbs

115 kg

## Performance Testing

### STATIC LOAD / ASTM F970

Passes

### FLEXIBILITY / ASTM F137

Passes

### RESISTANCE TO CHEMICALS / ASTM F925

Passes

### RADIANT PANEL / ASTM E648

Passes, Class I

### SLIP RESISTANCE / ASTM D2047

>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

## Warranty

10 Year Limited Commercial.

Please visit [patcraft.com](http://patcraft.com) for the most current warranty information.

# R | BOUNCE BACK 6.5

## Installation Methods



Non-Reverse

[Installation Guidelines](#)

[Maintenance Guidelines](#)

## Environmental

FLOORSCORE®

Certified