	CRIOR DESIGN FINISH LISTING		
DESCRIPTION	NO. DESCRIPTION		
FIELD LVT: TARKETT, STYLE: ID LATITUDES ABSTRACTS, COLOR: VILLA WHITE PLCZ 7563, SIZE: 6x36 (18x18 AT LOBBY 270), THICKNESS: 3MM, WEAR LAYER: 20MIL	TYPICAL FIELD PAINT: SHERWIN WILLIAMS - EGRET WHITE 7570		
ACCENT LVT: TARKETT, STYLE: ID LATITUDES ABSTRACTS, COLOR: LANDMARK PLCZ 7565, SIZE: 6x36 (18x18 AT LOBBY 270), THICKNESS: 3MM, WEAR LAYER: 20MIL	TRIM PAINT (HM DOORS AND WINDOWS): SHERWIN WILLIAMS - COURTYARD 6440		
ACCENT LVT: TARKETT, STYLE: ID LATITUDES ABSTRACTS, COLOR: COASTLINE PLCZ 7556, SIZE: 6x36 (18x18 AT LOBBY 270), THICKNESS: 3MM, WEAR LAYER: 20MIL	P3 CEILING PAINT: SHERWIN WILLIAMS - PURE WHITE 7005		
PATTERN: LV1-IS ALWAYS THE FIELD TILE. PATTERN COLORS: V1-3 AS LISTED IN INDEX TO ROOM FINISH SCHEDULE ABOVE, SEE FINISH FLOOR PLANS FOR PATTERN.	ACCENT PAINT: SHERWIN WILLIAMS - CILANTRO 6453		
EPOXY FLOORING & INTEGRAL 6" BASE: KEY RESIN — COLOR: SELECTED BY ARCHITECT FROM MANUFACTURERS STANDARD COLORS	TA WALL THE THE AT WATER COUNTAINS OF COLUMN AND COLOR DATING A CO		
RUBBER BASE: JOHNSONITE — TRADITIONAL TOE BASE, 4" HEIGHT, COLOR: GREEN VISTA VN4	WALL TILE: TILE AT WATER FOUNTAINS - CROSSVILLE, RETRO ACTIVE 2.0, (T1A) COLOR - RACING GREEN PATTERN, (T1B) COLOR - ARMOR PATTERN, SIZE: 4x12 - SEE ELEVATION 2/D2100 FOR INSTALL PATTERN GT GROUT: CUSTOM BUILDING PRODUCTS - CEG-LITE 100% SOLIDS COMMERCIAL EPOXY GROUT - COLOR: SELECTED BY ARCHITECT FROM MANUFACTURERS STANDARD COLORS		
RUBBER BASE: JOHNSONITE — TRADITIONAL TOE BASE, 6" HEIGHT, COLOR: GREEN VISTA VN4			
	A1 ACOUSTIC CEILING TILE: ARMSTRONG - FINE FISSURED, MODEL: 1717, SIZE: 24"x24"x3/4", EDGE PROFILE: ANGLED TEGULAR FOR INTERFACE WITH PRELUDE XL 15/16" EXPOSED TEE, COLOR: WHITE		
RUBBER STAIR TREAD & RISER: TARKETT - VISUALLY IMPAIRED RUBBER STAIR TREAD WITH INTEGRATED RISER, COLOR: OAK VALLEY, TEXTURE: HAMMERED, ACCENT STRIP: 40 BLACK	ACOUSTIC CEILING TILE: KITCHEN - ARMSTRONG - CLEAN ROOM VL, MODEL: 868, SIZE: 24"x24"x5/8", EDGE PROFILE: SQUARE LAY-IN FOR INTERFACE WITH PRELUDE PLUS XL FIRE GUARD 15/16" EXPOSED TEE. COLOR: WHITE		
INTERMEDIATE STAIR LANDINGS RUBBER FLOORING: TARKETT — COLORSPLASH RUBBER TILE, COLOR: VINEYARD			
SOLID SURFACE: CORIAN — SILVER LINEAR	WOOD INTERIOR DOORS: MARSHFIELD DOOR SYSTEMS - SPECIES: WHITE MAPLE, DESIGNER COLOR: CARAMEL		
) LAMINATE AT CABINETRY COUNTERTOP: WILSONART - HANDSPUN CHESTNUT 5036-38	WOOD CABINETRY AND CASEWORK: MATCH PRE-FINISHED WOOD DOOR STAIN		
	INSTALL EPOXY WALL COATING, GLASLOK 270 FR HIGH BUILD OR EQUAL, ON WALLS ABOVE CUSTODIAL FLOOR SINKS, ALL SHOWER WALLS INSIDE STALL, AND ALL URINAL PARTITION WALLS. COATING SHALL WRAP END OF PARTITION WALL WHERE TWO SHOWER/URINAL STALLS ADJOIN EACH OTHER. FINISHED HEIGHTS SHALL BE 7'-4" AFF.		

FINISH & ACCENT LEGEND XX XX ACCENT AND/OR SPECIFIC FINISH THIS FINISH & ACCENT FINISH LEGEND IS ONLY A FLOORING TRANSITION BETWEEN DIFFERENT FINISH MATERIALS SYMBOLIC REPRESENTATION OF DIFFERENT MATERIAL TYPES USED FOR THIS PROJECT. WOOD GRAIN DIRECTION THE CONTRACTOR SHALL REFER TO THE INTERIOR DESIGN FINISH LISTING ON SHEET DOOOD THE INTERIOR DESIGN DRAWINGS, AND THE SPECIFICATIONS FOR ADDITIONAL INDICATES ROLLER SHADE. SEE SPECIFICATION 122413 PRODUCT AND COLOR IDENTIFICATION.

	TERIOR	DESIG		INISH .	ABBREVI	ATIONS
A AP BD CPT DP EF EPX EXIST EXP GLF GT IB LVT MEX MTL OF/CI OF/OI	ACOUSTICAL CEILING TILE ACOUSTICAL PANEL MARKER BOARD/CORK BOARD CARPET DECORATIVE PANEL EPOXY FLOORING EPOXY PAINT EXISTING TO REMAIN EXPOSED STRUCTURE GLASS FILM GROUT INTEGRAL BASE LUXURY VINYL TILE MATCH EXISTING METAL OWNER FURNISHED/ CONTRACT		P P CONC. PL R RB RF RS RW SEAL CONC. SS S STL S STLB ST SV SVT T TB	PAINT PAINTED CONCRETE PLASTIC LAMINATE RUBBER FLOORING RESILIENT BASE RESINOUS FLOORING ROLLER SHADE RESIN WALL SEALED CONCRETE SOLID SURFACE MATERIAL STAINLESS STEEL STAINLESS STEEL BASE STAIN SHEET VINYL SOLD VINYL TILE TILING (CERAMIC/PORCEL TILE BASE (CERAMIC/POR	AIN/ETC.)	TERRAZZO FLOORING TACK BOARD TACKABLE WALL PANEL UPHOLSTERY VINYL COMPOSITION TILE VINYL WALL COVERING WOOD WALK OFF MAT WALL SAFETY PAD

1. THE CONTRACTOR SHALL NOT SCALE DRAWINGS. IF DIMENSIONS ARE IN QUESTION, THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING CLARIFICATION FROM THE INTERIOR DESIGNER BEFORE

THE CONTRACTOR SHALL NOTIFY THE INTERIOR DESIGNER OF ITEMS REQUIRING FINISH SELECTIONS THAT ARE NOT CLARIFIED IN THE CONTRACT DOCUMENTS OR IN THE PROJECT MANUAL.

THE CONTRACTOR SHALL NOTIFY THE INTERIOR DESIGNER IF ANY WORK INDICATED IN THE CONTRACT DOCUMENTS CAN NOT BE PERFORMED DUE TO EXISTING FIELD CONDITIONS.

4. SEE SPECIFICATION MANUAL FOR ADDITIONAL FINISH INFORMATION.

RESILIENT TILE FLOORING

SEE FLOOR PATTERN PLANS IN INTERIOR DESIGN DRAWINGS FOR FLOOR PATTERNS. ENSURE THAT ALL FLOOR TILE JOINTS ARE STRAIGHT AND ALIGNED.

IF ANY DIMENSIONS OR CONDITIONS OF FLOOR TILE INSTALLATION ARE IN QUESTION, CONTACT INTERIOR DESIGNER FOR CLARIFICATION. WHERE FLOOR TILES ARE CENTERED WITHIN A SPACE, ENSURE ALL PERIMETER AND/OR BORDER TILES AT WALLS ARE OF EQUAL DEPTH.

ANY TILE CRACKED OR CHIPPED DURING OR AFTER INSTALLATION BUT BEFORE DATE OF MATERIAL COMPLETION SHALL BE REPLACED.

1. SEE FINISH LISTING FOR GROUT SELECTION.

SEE CABINET ELEVATIONS & INTERIOR ELEVATIONS FOR TILE DETAIL AND LAYOUT INFORMATION. 3. GROUT JOINTS OF FLOOR, BASE AND WALL TILE SHALL ALL ALIGN.

1. ALL FLOORING TRANSITIONS SHALL OCCUR AT THE CENTERLINE OF ALL DOORS, UNLESS OTHERWISE DESIGNATED BY FLOOR TRANSITION SYMBOLS ON THE FINISH PLANS. INSTALL METAL EDGE TRANSITION STRIP WHERE EPOXY FLOOR MEETS RESILIENT TILE OR OTHER FLOORING THAT FINISHES FLUSH WITH TOP OF TILE.

WALL BASE 1. INTEGRAL EPOXY BASE SHALL BE USED IN ALL WET AREAS WHERE EPOXY FLOOR IS SPECIFIED.

2. SEE FINISH LISTING ON INTERIOR DESIGN SHEET DOODO FOR BASE DESIGNATIONS. INTERIOR PAINTING

1. IF ADJACENT WALL IS SCHEDULED TO HAVE A PAINT FINISH, PAINT VERTICAL AND HORIZONTAL SURFACES OF BULKHEADS AND SOFFITS TO MATCH WALL PAINT FINISH, UNLESS OTHERWISE NOTED. 2. WALLS IN ALL SPACES WITH EXPOSED CEILINGS SHALL BE PAINTED UP TO THE UNDERSIDE OF FLOOR/ROOF SLAB ABOVE. 3. ALL WALLS SHALL BE P-1, UNLESS OTHERWISE NOTED

WINDOWS, DOORS, DOOR FRAMES, ACCESS DOORS, ETC. 1. CONTRACTOR SHALL PAINT ALL METAL ACCESS DOORS, ELECTRICAL PANELS, RECESSED CABINET FACES, HVAC REGISTERS, GRILLES, ETC. TO MATCH ADJACENT WALL COLOR, UNLESS OTHERWISE

NOTED. ELECTRICAL PANELS ARE NOT REQUIRED TO BE PAINTED WITHIN ELECTRICAL ROOMS. EXPOSED CONDUITS ARE REQUIRED TO BE PAINTED.

2. INTERIOR HOLLOW METAL DOORS, DOOR FRAMES, WINDOW FRAMES AND VIEW WINDOW FRAMES SHALL BE PAINTED P2, U.O.N..

3. EXTERIOR SIDE OF HOLLOW METAL DOORS AND TRIM TO BE PAINTED, COLOR: AS SPECIFIED BY ARCHITECT FROM MANUFACTURER'S STANDARD COLORS. INTERIOR ARCHITECTURAL WOODWORK

1. SEE CABINETWORK/CASEWORK ELEVATIONS FOR SPECIFIC FINISH LOCATIONS ON CABINETWORK/CASEWORK

2. SEE SPECIFICATION FOR CABINETWORK/CASEWORK HARDWARE REQUIREMENTS.

1. GYPSUM BOARD CEILINGS SHALL BE PAINTED P-3, UNLESS OTHERWISE NOTED. REFER TO FINISH PLANS FOR SOFFIT ACCENT COLORS.
2. WHERE SOFFITS ARE NOTED TO BE PAINTED AN ACCENT COLOR, PAINT HORIZONTAL AND ALL EXPOSED VERTICAL FACES ACCENT COLOR, U.O.N.

10/18/2024

FACILITY CODE 650-1050 IU'S 18 FTE 275

DRAWINGS ARE THE PROPERTY OF THE ARCHITECT AND SHALL NOT BE REPRODUCED OR USED WITHOUT WRITTEN PERMISSION AND CREDIT © 2024 ALTMAN + BARRETT ARCHITECTS, P.C.

PROJECT NO: 23030