BID ON: WOOD DOORS - MAINT. DEPT. BID NO.: 23-20

	QTY	BIDDER	UNIT COST	BRAND/MODEL	DELIVERY TIME AFTER RECEIPT OF P.O.
AS NEEDED					
Composite solid wood doors 3070 with wide bottom rail Engineered composite hardwood core with "A" or "B" grade face. ADHESIVES: Face to core and frame type I. Plywood faces type I or type II by specification. All adhesives are formulated using no formaldehyde. AESTHETIC QUALITY STANDARDS: Mill grade aesthetics per WDMA I.S. 1-A Type SCL-7 and FD 20-7 with softwood stile. PERFORMANCE STANDARDS: Extra heavy duty per WDMA I.S. 1-A Flush Wood Door Performance Standards. Assembly: Bonded. Frame components are bonded to core. Components are assembled to meet or exceed 20 minute fire door specification for UL10b or UL10c fire test requirements. Both faces of the assembly are uniformly sanded prior to application of the door faces. WARRANTY: Standard interior product to be warranted for the lifetime of the original installation. When specified for exterior applications product should be warranted for one year of the original installation. The product must be specified to have type I adhesives used in the construction of the door faces. The product must also be installed utilizing proper flashing and finishes.	As Needed	Brabner & Hollon	\$352.00	Masonite	8-10 Weeks
	AS NEEDED Composite solid wood doors 3070 with wide bottom rail Engineered composite hardwood core with "A" or "B" grade face. ADHESIVES! Face to core and frame type I. Plywood faces type I or type II by specification. All adhesives are formulated using no formaldehyde. AESTHETIC QUALITY STANDARDS! Mill grade aesthetics per WDMA I.S. 1-A Type SCL-7 and FD 20-7 with softwood stile. PERFORMANCE STANDARDS! Extra heavy duty per WDMA I.S. 1-A Flush Wood Door Performance Standards. Assembly: Bonded. Frame components are bonded to core. Components are assembled to meet or exceed 20 minute fire door specification for UL10b or UL10c fire test requirements. Both faces of the assembly are uniformly saded prior to application of the door faces. WARNANY! Standard interior product to be warranted for the lifetime of the original installation. When specified for exterior applications product should be warranted for one year of the original installation. The product must be specified to have type I adhesives used in the construction of the door faces. The product	AS NEEDEDComposite solid wood doors 3070 with wide bottom rail Engineered composite hardwood core with "A" or "B" grade face.As NeededADHESIVES:Sace to core and frame type I. Plywood faces type I or type II by specification. All adhesives are formulated using no formaldehyde.ASTHETIC QUALITY STANDARDS:Mill grade aesthetics per WDMA I.S. 1-A Type SCL-7 and FD 20-7 with softwood stile.FRFORMANCE STANDARDS:Extra heavy duty per WDMA I.S. 1-A Flush Wood Door Performance Standards.Assembly:Bonded. Frame components are bonded to core.Components are assembled to meet or exceed 20 minute fire door specification for UL10b or UL10c fire test requirements. Both faces of the assembly are uniformly sanded prior to application of the door faces.WARRANTY:Standard interior product to be warranted for the lifetime of the original installation.When specified for exterior applications product should be warranted for one year of the original installation.The product must be specified to have type I adhesives	AS NEEDED Composite solid wood doors 3070 with wide bottom rail Engineered composite hardwood core with "A" or "B" grade face. ADHESIVESI Tace to core and frame type I. Plywood faces type I or type II by specification. All adhesives are formulated using no formaldehyde. AESTHETIC QUALITY STANDARDSI Mill grade aesthetics per WDMA I.S. 1-A Type SCL-7 and FD 20-7 with softwood stile. PERFORMANCE STANDARDSI Extra heavy duty per WDMA I.S. 1-A Flush Wood Door Performance Standards. Assembly: Bondel. Frame components are bonded to core. Components are assembled to meet or exceed 20 minute fire door specification of the door faces. MILL of the original installation. Menspecified for exterior applications product should be waranted for one year of the original installation. The product must be specified to have type I adhesives ued in the construction of the door faces. The product	AS NEEDED Composite solid wood doors 3070 with wide bottom rait Engineered composite hardwood core with "A" or "B" grade face. AS Brabner & Hollon \$352.00 Needed Readed Readed Sature Section 100 Section	AS NEEDED Composite solid wood doors 3070 with wide bottom rail Engineered composite hardwood core with "A" or "B" As Brabner & Hollon \$352.00 Masonite Store and frame type I. Plywood faces type I or type I by specification. All adhesives are formulated using no formaldehyde. ASTHETIC QUALITY STANDARDS Mil grade aesthetics per WDMA 1.S. 1-A Type SCI-57 and P2.07 with softwood stile. PROFMANCE STANDARDS Mathematical Store and St

VENDOR ADDRESS

#579 BRABNER & HOLLON 3053 COTTON STREET MOBILE, AL 36607 (251) 479-5408 PHONE (251) 479-5403 FAX